



Model: WS NC FOR RTI KA8

Family: WALL-SMART

DWG NO. 027-4-486-SPC



Model No.: 027-1-486

PRODUCT SPEC.

REVISION A

DATE 24/JUNE/2019

Make Your Wall Smart

WS NC FOR RTI KA8 - Product description:

The "WS NC FOR RTI KA8" is an adapter for in-wall flush installation of a KA8 Touch panel.

The "WS NC FOR RTI KA8" firmly mounts the touch panel while allowing easy access, insertion and removal.

Key features and benefits:

- Flush with the wall.
- Paintable with the wall paint in any color and texture.
- Allows easy insertion and removal of the panel by manual push and magnet detachment of the touch panel adapter.
- The adapter is supplied unpainted (To be painted after installation as part of the wall).
- Includes depth calibration mechanism.
- Designed to be installed in 1/2" drywall. Installation of the Wall-Smart adapter is straight-forward. Installation process is similar to drywall construction procedures. Before installation, read Wall-Smart installation instruction 10-04-00101-INS in <http://www.wall-smart.com/faq>
- For installation in concrete/block wall use "WS CONCRETE BOX 300X225" P/N 10-01-446 (sold separately) according installation instruction 10-04-00103-INS in <http://www.wall-smart.com/faq>
- Designed for the use with KA8 Touch panel (by rti) (Touch panel not included).
- Adapter kit contains:

1. (X1) Wall adapter;
2. (X1) Touch screen adapter
3. (X4) M4 nuts
4. (X4) M4X10 SCREWS

Key properties:

- Dimensions (W/H/D): 299.3mm (11.78")/ 224.3mm (8.83")/ 46.2mm (1.82")
- Power Supply: None (manual adapter).
- Weight: 0.95Kg, 2.1lbs.
- Material: Moisture resistant MDF (compliant with TSCA Title VI)
- To be installed in 1/2" drywall (for installation in 5/8" drywall use 1/8" shim pack P/N 10-01-067 (sold separately)).

