



Model: WS NC FOR BLACK NOVA
1MODULE LOW V

Model No.: 084-1-245

Family: WALL-SMART

DWG NO. 084-4-245-SPC

PRODUCT SPEC.

REVISION A

DATE 25/JULY/2021



Make Your Wall Smart

“WS NC FOR BLACK NOVA 1MODULE LOW V” - Product description:

The “WS NC FOR BLACK NOVA 1MODULE LOW V” is an adapter for in-wall flush installation of a BLACK NOVA 1module low voltage keypad.

The “WS NC FOR BLACK NOVA 1MODULE LOW V” firmly mounts the keypad allowing easy access, insertion and operation.

Key features and benefits:

- Flush with the wall.
- Paintable with the wall paint in any color and texture.
- Includes depth calibration mechanism.
- Allows easy insertion and removal of the keypad.
- The adapter is supplied unpainted (To be painted after installation as part of the wall).
- Designed to be installed in 1/2” drywall. Installation of the Wall-Smart adapter is straight-forward. Installation process is similar to drywall construction procedures. Before installation, read Wall-Smart installation instruction 10-04-00101-INS in <http://www.wall-smart.com/faq>
- For installation in concrete/block wall use “CONCRETE BOX 165X165” P/N 10-01-521 (sold separately) according installation instruction 10-04-00103-INS in <http://www.wall-smart.com/faq>
- Designed for the use with 1module low voltage keypad (by BLACK NOVA) (not included).
- Adapter kit contains:
 1. Wall adapter (x1)
 2. Keypad adapter (x1)
 3. CS M3X10 Screws (x4)
 4. M3 Nuts (x4)

Key properties:

- Dimensions (W/H/D): 163mm (6.42”)/ 163mm (6.42”)/ 44mm (1.73”)
- Power Supply: None (manual adapter).
- Weight: 0.5Kg, 1.10lbs.
- Material: Moisture resistant MDF.
- To be installed in 1/2” drywall (for installation in 5/8” drywall use 1/8” shim pack P/N 10-01-067 (sold separately)).

