

Model: WS for Lithoss SB\_T Button switch

Family:

**WALL-SMART** 

DWG NO. 10-04-167-SPC

PRODUCT SPEC

REVISION

DATE 01/May/2014

### **Make Your Wall Smart**

# WS for Lithoss SB\_T Button switch - Product description:

The WS for Lithoss SB\_T Button switch is an adapter for in-wall flush installation of a Lithoss SB T Button switch.


The WS for Lithoss SB\_T Button switch securely mounts the keypad while allowing easy access, insertion and removal.


#### Key features and benefits:


- Flush with the wall.
- Paintable with the wall paint in any color and texture.
- Allows easy insertion and exertion of the keypad by manual push and magnet detachment of the keypad tray.
- The adapter is supplied unpainted (To be painted after installation as part of the wall).
- Designed to be installed in 1/2" drywall. Installation of the Wall-Smart adapter is straight-forward. Installation process is similar to drywall construction procedures. Before installation, read Wall-Smart installation instruction 10-04-00101-INS in http://www.wallsmart.com/fag
- For installation in concrete/block wall use "WS Concrete Box 147x147" P/N 10-01-114 (sold separately) according installation instruction 10-04-00103-INS in http://www.wall-smart.com/faq
- Designed for the use with Lithoss SB T Button switch keypad (keypad not included).
- Adapter kit contains:
  - Wall adapter (item 2)
  - Keypad adapter (item 1)
  - (2x) M3 Screw (item 4)
  - (2x) M3 Nut (item 3)


# **Key properties:**

- Dimensions (W/H/D): 147mm (5.8")/ 147mm (5.8")/ 22mm (0.87")
- Power Supply: None (manual adapter).
- Weight: 0.39Kg, 0.86lbs.











by Wall-Smart

UNI ESS OTHERWISE SPECIFIED DIMENSIONS ARE IN MILLIMETERS

Phone: (201) 205-2056 / info@wall-smart.com

INFORMATION CONTAINED HEREIN IS PROPRIETARY AND MAY NOT BE USED, REPRODUCED OR COPIED WITHOUT WRITTEN CONSENT OF WALL-SMART **©**