



Model: WS NC For RTI KX4

Family: WALL-SMART

DWG NO. 027-4-979-SPC

Model No.: 027-1-979

PRODUCT SPEC.

REVISION A

DATE 10/OCT./2023



Make Your Wall Smart

WS NC For RTI KX4 - Product description:

The "WS NC For RTI KX4" is an adapter for in-wall flush installation of a KX4 4 inch In-Wall Touchpanel Keypad w/ Control Processor (by RTI).

The "WS NC For RTI KX4" firmly mounts the keypad while allowing easy access, insertion and removal.

Key features and benefits:

- Flush with the wall.
- Paintable with the wall paint in any color and texture.
- Includes depth calibration mechanism.
- The adapter is supplied unpainted (To be painted after Installation as part of the wall).
- Designed to be installed in 1/2" drywall. Installation of the Wall-Smart adapter is straight-forward. Installation process is similar to drywall construction procedures. Before installation, read Wall-Smart installation instruction 10-04-00101-INS in <http://www.wall-smart.com/faq>
- For installation in concrete/brick wall use "WS concrete box 224x194" P/N 10-01-638 (sold separately) according installation instruction 10-04-00103-INS in <http://www.wall-smart.com/faq>
- Designed for the use with KX4 4 inch In-Wall Touchpanel Keypad w/ Control Processor (by RTI) (not included).
- Adapter kit contains:

1. (X1) Wall adapter

Key properties:

- Dimensions (W/H/D): 192mm (7.56")/ 222mm (8.74")/ 33.2mm (1.31").
- Power Supply: None (manual adapter).
- Weight: 0.42Kg, 0.92lbs.
- Material: Moisture resistant MDF (compliant with TSCA Title VI).
- To be installed in 1/2" drywall (for installation in 5/8" drywall use 1/8" shim pack P/N 10-01-067 (sold separately)).

