



Model: WS NC FOR RING ALARM KEYPAD 2ND GEN

Model No.: 005-1-993

Family: WALL-SMART

DWG NO. 005-4-993-SPC

PRODUCT SPEC.

REVISION A

DATE 20/Aug/2024



Make Your Wall Smart

“WS NC FOR RING ALARM KEYPAD 2ND GEN” - Product description:

The “WS NC FOR RING ALARM KEYPAD 2ND GEN” is an adapter for in-wall flush installation of Ring alarm keypad 2nd gen. The “WS NC FOR RING ALARM KEYPAD 2ND GEN” firmly mounts the alarm keypad while allowing easy access, insertion and operation.

Key features and benefits:

- Flush with the wall.
- Paintable with the wall paint in any color and texture.
- Includes depth calibration mechanism.
- Allows easy insertion and removal of the alarm keypad.
- The adapter is supplied unpainted (To be painted after installation as part of the wall).
- Designed to be installed in ½” drywall. Installation of the Wall-Smart adapter is straight-forward. Installation process is similar to drywall construction procedures. Before installation, read Wall-Smart installation instruction 10-04-00101-INS in <http://www.wall-smart.com/faq>
- For installation in concrete/block wall use “WS Concrete box 183x186” P/N 100-1-024 (sold separately) according installation instruction 10-04-00103-INS in <http://www.wall-smart.com/faq>
- Designed for the use with Ring alarm keypad 2nd gen. (Ring alarm keypad is not included).
- Adapter kit contains:
 1. Wall adapter (X1)
 2. Alarm keypad adapter (X1)

Key properties:

- Dimensions (W/H/D): 180.4mm (7.1”)/ 184.4mm (7.26”)/ 44mm (1.73”)
- Power Supply: None (manual adapter).
- Weight: 0.5Kg, 1.1lbs.
- Material: Moisture resistant MDF (compliant with TSCA Title VI).
- To be installed in ½” drywall (for installation in 5/8” drywall use 1/8” shim pack P/N 10-01-067 (sold separately)).

