



Model: WS NC FOR SAVANT WPB-XXLV

Family: WALL-SMART

DWG NO. 028-4-855-SPC



Model No.: 028-1-855

PRODUCT SPEC.

REVISION A
DATE 30/SEP./2020

Make Your Wall Smart

“WS NC FOR SAVANT WPB-XXLV” - Product description:

The “WS NC FOR SAVANT WPB-XXLV” is an adapter for in-wall flush installation of WPB-XXLV keypad.

The “WS NC FOR SAVANT WPB-XXLV” firmly mounts the keypad while allowing easy access, insertion and operation.

Key features and benefits:

- Flush with the wall.
- Paintable with the wall paint in any color and texture.
- Allows easy insertion and removal of the keypad.
- The adapter is supplied unpainted (To be painted after installation as part of the wall).
- Designed to be installed in ½” drywall. Installation of the Wall-Smart adapter is straight-forward. Installation process is similar to drywall construction procedures. Before installation, read Wall-Smart installation instruction 10-04-00101-INS in <http://www.wall-smart.com/faq>
- For installation in concrete/block wall use “WS Concrete Box 200x160” P/N 10-01-181 (sold separately) according installation instruction 10-04-00103-INS in <http://www.wall-smart.com/faq>
- Designed for low voltage only
- Designed for the use with WPB-XXLV keypad (by Savant) (keypad not included).
- Adapter kit contains:
 1. Wall adapter;
 2. keypad adapter;
 3. (X2) M3x12 screws;
 4. (X2) M3 nuts;

Key properties:

- Dimensions (W/H/D): 198mm (7.80")/ 158mm (6.22")/ 22mm (0.87")
- Power Supply: None (manual adapter).
- Weight: 0.3Kg, 0.66lbs.
- Material: Moisture resistant MDF (compliant with TSCA Title VI)
- To be installed in ½” drywall (for installation in 5/8” drywall use 1/8” shim pack P/N 10-01-067 (sold separately)).

