



Model: WS NC FOR ABB 4M
TBR/U4.8.1-CG Touch control

Family: WALL-SMART

DWG NO. 070-04-694-SPC



Model No.: 070-1-694

PRODUCT SPEC.

REVISION A
DATE 18/MAR/2020

Make Your Wall Smart

WS NC FOR ABB 4M TBR/U4.8.1-CG Touch control - Product description:

The "WS NC FOR ABB 4M TBR/U4.8.1-CG Touch control" is an adapter for in-wall flush installation of an ABB 4M TBR/U4.8.1-CG Touch control. The "WS NC FOR ABB 4M TBR/U4.8.1-CG Touch control" firmly mounts the control element while allowing easy access, insertion and removal.

Key features and benefits:

- Flush with the wall.
- Paintable with the wall paint in any color and texture.
- Allows easy insertion and removal of the keypad by manual push.
- The adapter is supplied unpainted (To be painted after installation as part of the wall).
- Designed to be installed in 1/2" drywall. Installation of the Wall-Smart adapter is straight-forward. Installation process is similar to drywall construction procedures. Before installation, read Wall-Smart installation instruction 10-04-00101-INS in <http://www.wall-smart.com/faq>
- For installation in concrete/block wall use "WS CONCRETE BOX 159x230" P/N 100-1-602 (sold separately) according installation instruction 10-04-00103-INS in <http://www.wall-smart.com/faq>
- Designed for the use with ABB 3M TBU6.8.1-CG Touch control (not included).
- Adapter kit contains:

1. (X1) Wall adapter;
2. (X1) Touch screen adapter
3. (X4) M3 nuts
4. (X4) M3X12 SCREWS

Key properties:

- Dimensions (W/H/D): 228mm (8.98")/ 157mm (6.18")/ 22mm (0.87")
- Power Supply: None (manual adapter).
- Weight: 0.6Kg, 1.32 lbs.
- Material: Chemically treated, Moisture resistant MDF

