

## **Make Your Wall Smart**

## WS NC FOR SAVANT ITP-E5500 5.5" SCREEN - Product description:

The "WS NC FOR SAVANT ITP-E5500 5.5" SCREEN" is an adapter for in-wall flush installation of a ITP-E5500 Touch Screen.

The "WS NC FOR SAVANT ITP-E5500 5.5" SCREEN" firmly mounts the touch screen while allowing easy access, insertion and removal.


## Key features and benefits:

- Flush with the wall.
- Paintable with the wall paint in any color and texture.
- Allows easy insertion and removal of the keypad by manual push and magnet detachment of the Touch Screen tray.
- The adapter is supplied unpainted (To be painted after installation as part of the wall).
- Includes depth calibration mechanism.
- Designed to be installed in ½" drywall. Installation of the Wall-Smart adapter is straight-forward. Installation process is similar to drywall construction procedures. Before installation, read Wall-Smart installation instruction 10-04-00101-INS in http://www.wallsmart.com/faq
- For installation in concrete/block wall use "WS CONCRETE BOX 164X225" P/N 10-01-445 (sold separately) according installation instruction 10-04-00103-INS in http://www.wall-smart.com/faq
- Designed for the use with ITP-E5500 Touch Screen (by SAVANT) (Touch Screen not included).
- Adapter kit contains:
  - 1. (X1) Wall adapter;
  - 2. (X1) Touch screen adapter
  - 3. (X2) M3 nuts
  - 4. (X2) M3X12 SCREWS


Phone: (201) 205-2056 / info@wall-smart.com


## **Key properties:**

- Dimensions (W/H/D): 163.3mm (6.43")/ 224.3mm (8.83")/ 42.8mm (1.69")
- Power Supply: None (manual adapter).
- Weight: 0.6Kg, 1.32lbs.



www.wall-smart.com





INFORMATION CONTAINED HEREIN IS PROPRIETARY AND MAY NOT BE USED, REPRODUCED OR COPIED WITHOUT WRITTEN CONSENT OF WALL-SMART

ITP-E5500 Wall-plate

DRYWALL STUDS PUSH TO OPEN

DEPTH CALIBRATION SCREWS

